

# FFUF

## HTTP OPTIONS

- Maximum recursion depth. (default: 0) — -recursion-depth
- Recursion strategy: "default" for a redirect based, and "greedy" to recurse on all matches (default: default) — -recursion-strategy
- Replay matched requests using this proxy. — -replay-proxy
- Target TLS SNI, does not support FUZZ keyword — -sni
- HTTP request timeout in seconds. (default: 10) — -timeout
- Target URL — -u
- Proxy URL (SOCKS5 or HTTP). For example: http://127.0.0.1:8080 or socks5://127.0.0.1:8080 — -x

- H — Header "Name: Value", separated by colon. Multiple -H flags are accepted.
- X — HTTP method to use
- b — Cookie data "NAME1=VALUE1; NAME2=VALUE2" for copy as curl functionality.
- d — POST data
- http2 — Use HTTP2 protocol (default: false)
- ignore-body — Do not fetch the response content. (default: false)
- r — Follow redirects (default: false)
- recursion — Scan recursively. Only FUZZ keyword is supported, and URL (-u) has to end in it. (default: false)

## GENERAL OPTIONS

- Maximum running time in seconds per job. (default: 0) — -maxtime-job
- Disable the interactive console functionality (default: false) — -noninteractive
- Seconds of `delay` between requests, or a range of random delay. For example "0.1" or "0.1-2.0" — -p
- Rate of requests per second (default: 0) — -rate
- Do not print additional information (silent mode) (default: false) — -s
- Stop on all error cases. Implies -sf and -se. (default: false) — -sa
- Stop on spurious errors (default: false) — -se
- Stop when > 95% of responses return 403 Forbidden (default: false) — -sf
- Number of concurrent threads. (default: 40) — -t
- Verbose output, printing full URL and redirect location (if any) with the results. (default: false) — -v

- V — Show version information. (default: false)
- ac — Automatically calibrate filtering options (default: false)
- acc — Custom auto-calibration string. Can be used multiple
- ach — Per host autocalibration (default: false)
- ack — Autocalibration keyword (default: FUZZ)
- acs — Autocalibration strategy: "basic" or "advanced" (default: basic)
- c — Colorize output. (default: false)
- config — Load configuration from a file
- json — JSON output, printing newline-delimited JSON records (default: false)
- maxtime — Maximum running time in seconds for entire process. (default: 0)

## MATCHER OPTIONS

- Match HTTP response size — -ms
- Match how many milliseconds to the first response byte, either greater or less than. EG: >100 or <100 — -mt
- Match amount of words in response — -mw

- mc — Match HTTP status codes, or "all" for everything. (default: 200,204,301,302,307,401,403,405,500)
- ml — Match amount of lines in response
- mmode — Matcher set operator. Either of: and, or (default: or)
- mr — Match regexp

## FILTER OPTIONS

- Filter HTTP response size. Comma separated list of sizes and ranges — -fs
- Filter by number of milliseconds to the first response byte, either greater or less than. EG: >100 or <100 — -ft
- Filter by amount of words in response. Comma separated list of word counts and ranges — -fw

- fc — Filter HTTP status codes from response. Comma separated list of codes and ranges
- fl — Filter by amount of lines in response. Comma separated list of line counts and ranges
- fmode — Filter set operator. Either of: and, or (default: or)
- fr — Filter regexp

## INPUT OPTIONS

- Shell to be used for running command — -input-shell
- Multi-wordlist operation mode. Available modes: clusterbomb, pitchfork, sniper (default: clusterbomb) — -mode
- File containing the raw http request — -request
- Protocol to use along with raw request (default: https) — -request-proto
- Wordlist file path and (optional) keyword separated by colon. eg. '/path/to/wordlist:KEYWORD' — -w

- D — DirSearch wordlist compatibility mode. Used in conjunction with -e flag. (default: false)
- e — Comma separated list of extensions. Extends FUZZ keyword.
- ic — Ignore wordlist comments (default: false)
- input-cmd — Command producing the input. --input-num is required when using this input method. Overrides -w.
- input-num — Number of inputs to test. Used in conjunction with --input-cmd. (default: 100)

## OUTPUT OPTIONS

- Output file format. Available formats: json, ejson, html, md, csv, ecsv (or, 'all' for all formats) (default: json) — -of
- Don't create the output file if we don't have results (default: false) — -or

- debug-log — Write all of the internal logging to the specified file.
- o — Write output to file
- od — Directory path to store matched results to.



@hackinarticles



<https://github.com/Ignitetechnologies>



<https://in.linkedin.com/company/hackingarticles>